

DZR-590 Servo Control High Speed Shrink Packaging Machine (Lower Feeding)



Applicable Scope: Shrink packaging in groups of food, pharmaceuticals and beverages, instant bowl noodles, milk tea cups, mosquito coils, wall paper, filters, electrical switches, batteries, plastic wraps, garbage bags, tissue-paper, kitchen reasoners, various sizes of cartons and boxes, stationeries, presswork's, hardware's, industrial parts, cosmetics and other commodities.

Feature

1. Color touch screen control system, driven by three servo motors, easy to operate, high stability, high packaging efficiency and low failure rate; bag length, speed and temperature can be individually adjusted, easy to operate and accurate.
2. Cut-proof safety clutch device, does not damage the packaging.
3. High sensitivity photoelectric eye color standard tracking, mathematically input the sealing position, so as to make the sealing position more accurate.
4. Temperature independent PID control, better suitable for various coating materials.
5. Positioning stop function, no sticking knife, no waste of film.
6. The transmission system is simple, reliable and easy to maintain.
7. Cut the product to be automatically reversed, restart directly after boot convenient operation.
8. Adding refuse recovery device to make the package more beautiful, save about 20% -30% of material compared with traditional folding film packing machine.
9. It is feasible to be equipped with a typewriter or inkjet printer, and it is unnecessary to use manual.
10. It has motor brake control, and the equipment reaction is sensitive.
11. High efficient double temperature zone of heat shrink furnace, high efficient hot air circulation, automatic temperature control, to ensure shrinkage quality.

Specification

Max Flim size		≤590mm	
Model		120	150
Packing size	L : Bag length	L:60mm-320mm	L:100mm-450mm
	W : width	w:10mm-200mm	w:10mm-200mm
	H : height	H:5mm-35mm	H:35mm-70mm
Packing speed		30-150(pack / min)	30-150(pack / min)
Flim type		PVC;POF	
Power consumption		Packaging machine : 4.75KW ; Shrinking machine : 13.5KW	
Power supply		Packaging machine:220V,50HZ/60HZ;Shrinking machine:380V, 50HZ/60HZ	
Envelop dimensions		4800x1170x1500mm	
Shrinking machine		Dimensions : 2600x600x1700mm	
Weight		Packaging machine : 1000KG	

Max Flim size		≤590mm		
Model		180	210	240
Packing size	L : Bag length	L:150mm-530mm	L:180mm-600mm	L:210mm-650mm
	W : width	w:10mm-200mm	w:10mm-200mm	w:10mm-250mm
	H : height	H:65mm-100mm	H:80mm-130mm	H:100mm-150mm
Packing speed		30-135(pack / min))	30-100(pack / min)	30-80(pack / min)
Flim type		PVC;POF		
Power consumption		Packaging machine : 4.75KW ; Shrinking machine : 13.5KW		
Power supply		Packaging machine:220V,50HZ/60HZ;Shrinking machine:380V, 50HZ/60HZ		
Envelop dimensions		4800x1170x1500mm		
Shrinking machine		Furnace channel size : 2300*250*200mm		
Weight		Shrinking machine : 600KG		