

KX-L12 Vertical Carton Opener/ Erector



Technical features:

- Adopt suction cup type to open the box, suck and form, fold the bottom and seal the bottom at the same time. Adopt PLC+touch screen control for easy operation
- When changing the carton specifications, manual adjustment is sufficient (only 2 to 3 minutes), and the operation is simple and convenient
- Adopt vertical carton storage design for easy material replenishment
- Automatic alarm when there is a lack of carton, reminding the operator to add carton
- Equipment fault information can be displayed on the touch screen for easy fault handling
- Adopt organic glass protective cover to avoid accidental operation
- Equipped with full box detection function, the machine automatically pauses when the cartons on the back-end assembly line are full
- Other options:
 - ①Tape missing detection
 - ②Tape broken detection
 - ③Add door opening shutdown
 - ④Specified brand of electrical components
 - ⑤Stainless steel body/customized color
 - ⑥Can be equipped with hot melt adhesive to seal the box
 - ⑦Can customize non-standard size equipment

Equipment parameters:

Model	KX-L12
Power supply	220V 50HZ 240W
Air supply	≥6Kg/cm ² 0.4m ³ /min
Applicable carton	L200~500xW150~400xH120~400mm
Speed	10-12Box/minute
Tape	W48~75mm * L900码 Paper coreφ75mm
Tape corner length	50~70mm
Carton storage	60-80pieces
Table height	≥600mm
Mechanical Dimensions	L1900xW2080xH1492mm
Mechanical weight	500Kg