



## *JSM-6040PE PE Film Shrink Packaging Machine*



### **Features:**

- \*Super large air volume fan, quickly cools and shapes the product after heat shrinkage
- \*Dual high-power motors ensure sufficient circulating air volume
- \*Japanese FUJI power main switch, quality assurance
- \*Adopting frequency converter to control stepless speed regulation
- \*Both the inlet and outlet of the furnace are equipped with insulation baffles
- \*Original imported insulation and low cost, greatly reducing heat loss
- \*There are multiple options available for both regular and compact shaft types, and small items can be packaged without displacement
- \*Equipped with bottom corner bolts, it can be used in conjunction with production lines of different heights
- \*Stainless steel heater, with fast heating and a service life of up to 5-10 years
- \*Worm gear reducer and high-power motor ensure smooth and vibration free transportation. The bottom is equipped with casters that allow the machine to move freely
- \*Specially designed air duct system ensures even heating of the product

### **Specifications:**

- Model: JSF-6040PE
- Horizontal height/length of feeding belt:  $850 \pm 50\text{mm}$
- Maximum packaging size: L is not limited to x W600 x H400
- Packaging speed: 0-12m/minute
- Use power supply, power: 3  $\Phi$ /380V 18KW
- Sealing and cutting time/temperature: 0-6s/0-250 °C
- Dimensions: L3000 x W970 x H1400
- Net weight: 370kg