



ST-6030AH L Feeding Sleeve Wrapper for Packing Rice Bags



L Feeding Sleeve Wrapper Without Tray Technical Features

Fully auto side-feeding + lane separating, suitable for sleeve-wrapping untraded beverage and other bottles or cans.

Versatile in packing size, three-blade design, seams tight and strong.

Shrink Tunnel Technical Features

Stainless heating tubes and strong blowing motor ensure high heating efficiency, large air volume and uniform air circulation.

Solid metal rods wrapped by heat-resistance silicone tubes make the Conveyor rollers strong and resilient.

SM-6040M has thick-shaft design, ensuring smooth conveyance.

Technical Parameters

Model	ST-6030AH	SM-6040M
Machine Dimensions (mm)	1695x2730x2039	2804x980x1687
Tunnel Chamber Size (mm)	/	1800x600x400
Max Packing Size (mm)	400x300x300	1300x400x300
Sealing Blade Size L (mm)	700	/
Temperature Range	0 - 200℃	0 - 400℃
Working Table Height (mm)	850 ± 50	850 ± 50
Capacity (pcs/m)	6-14	25-30
N.W. (kg)	490	600
Power (kw)	1.5	25
Power Source	3PH 220V/380V 50/60Hz	3PH 220V/380V 50/60Hz
Air Source (kg/cm ²)	6-8	/
Applicable Film	PE	PE