

ZH-100 Glue Sealing Box Packing Machine



Technical Overview:

1. Machine at the prevailing GMP standard workshop space site design, manufacture.
2. Separating the whole design of the various functional areas, the use of imported photoelectric eye tracking, testing automatic control machine operation.
3. When the product is automatically loaded into the plastic tray, you can achieve automatic entry box sealed box.
4. Full mechanical action of each station has a high electronic automatic synchronization, so that the machinery to run a more coordinated, more balanced, low noise.
5. This cartoning machine, easy to operate. PLC programmable control, touch interface.
6. The machine PLC automatic control system output interface, can achieve real-time back-packing equipment monitoring.
7. High degree of automation, control a wide range of high control precision, control response, and good stability.
8. Small number of parts, the machine is simple in structure, easy maintenance.
9. The machine is low decibel design (equipment working noise ≤ 75 Decibel).
10. The line of maximum production speed 120 boxes / min, stable production speed: 30 - 120 boxes / min.
11. The entire line foot plate with threaded height adjustable.

Main Performance Parameters:

Item / Model	SH100
Packing speed	30-100 boxes /min
Carton size range	L (50-250) mm×W (20-170) mm×H (15-70) mm
Tray Paper Requirements	250-450g/m ³
Sheet size range	L (100-260) mm×W (100-190) mm
Instruction paper requires	55-70 g/m ³
Motor power	1.5KW
Power supply type	three-phase four-wire380V 50Hz
Machine noise	≤80dB
Gas source	0.5-0.8 Mpa
Air consumption	120-160L/min
Dimensions	3500×1500×1600 mm
Weight	1200Kg