

Side Sealer Continuous Motion S-30A / S-50A / S-60A / F-50A



Based on the servo driven continuous motion side sealer, S-50A and F-50A offer a more economical packaging solution with servo controlled for customers. S-50 can also be equipped by various kinds of infeed system so as to minimize the budget cost by increasing machine flexibility. This series is mostly suitable for contract packagers covering a wide range of applications.

Feature:

- Speed up to 70ppm.
- Quick change of infeed system for different products
 1. Power conveyor provides the easiest connection with existing production line.
 2. Finger chain conveyor normally uses for printing product with addition friction feeder
 3. Flight bar conveyor applies to multipack of different products' height and shape.
- (F-50 contains finger chain conveyor infeed system only.)
- Simple setup system and operation through user friendly touch screen design.
- Ease to recall package memory on the touch screen.
- Diagnostic features on the touch screen

Model	S-30A	S-50A	S-60A	F-50A
Machine Size (mm) L x W x H	2295 x 1160 x 1370	4100 x 1610 x 1370	4250 x 1760 x 1370	4755 x 1660 x 1370
End Seal Bar (mm)	380	530	680	530
Packing Size (mm) L x W x H	(80~700) x (80~230) x (10~180)	(80~700) x (80~380) x (10~180)	(80~700) x (80~530) x (10~180)	(80~700) x (80~380) x (5~180)
Voltage	220V / 1PH	220V / 1PH	220V / 1PH	220V / 1PH
Power (Kw)	5 Kw	5 Kw	5Kw	5.5Kw
Pneumatic	55psi, 6kg/sq.cm	55psi, 6kg/sq.cm	55psi, 6kg/sq.cm	55psi, 6kg/sq.cm