

Granule Feed Bag Packing Machine MAC-8S-235



Equipment features:

1. Easy to operate touch screen menu, wide screen (10.4 inches);
2. Alarm and menu display, easy to solve machine problems;
3. Quickly change the package size within 10 minutes:

A: adjust 16 claw hands through the touch screen at the same time;

B: the size of the bag feeder is controlled by the screen and no tools are needed.

4. Automatic central lubrication system, easy to maintain;
5. The machine is waiting for the feeder to feed;
6. External parts 304 stainless steel, aluminum alloy oxidation;
7. Special design of sealing strip to achieve perfect sealing (one sealing station, one grid sealing station);
8. Memory maintenance function (seal temperature, machine speed, seal width);
9. The touch screen adjusts the sealing temperature;
10. Spring device ensures easy adjustment of seal;
11. The specially designed heating device ensures that the seal does not deform;
12. The bag feeder is easy to adjust and maintain;

Safety protection: low noise (65Db), very low vibration when the machine is running.

Machine specification:

The model is **MAC-8S-235**

1. Product: packaging bag (sample bag is needed eventually);
2. Filling capacity: 500g;
3. Speed: 40-55 bags/min. According to the packaging products, different bag sizes and material speed will be different.
4. Packaging bag: prefabricated bag
5. Bag size: width: 90-235mm, length: 320mm;
6. Bag material: composite film;
7. Sealing: continuous thermal sealing (sealing form: linear);
8. Sealing temperature: PID control (0-300 degrees);
9. Pressure: pressure seal;
10. Printing: inkjet printing (optional);
11. Bag feeder: belt type;
12. Bag change: 16 clips can be automatically adjusted through the touch screen