

TF6540+BS5540L Automatic Mantle Sealing and Cutting Packing Machine



Electric fully automatic machine from the process control and issued a warning and letters is no obstacle warning function. It is currently closed Reshousu packaging machine sets already more advanced packaging equipment. The aircraft mainly food, beverages, native products, ceramics and other items integrated sets of protective is fully automatic packaging. It apply to PE film packaging materials, packaging cartons compared to traditional, much of the packaging cost savings. Reshousuo with PE film packaging machine used for the packaging to complete integrity, a good contraction effects. And automatic production lines with the use of better reflect its superiority.

TF6540 STEAL AND CUTTING TECHNICAL SPECIATIONS

Model	TF6540
Voltage	AC 220/50~60 V 110/50~60 Hz
Power	1.5 KW
Max. Packing Dimension (L×W×H)	530×330×380 mm
packing Speed	12Pcs/min
Max. Sealing Length	650 mm
Working Air Pressure	6~8 Kgf/cm ²
Dimension (L×W×H)	1550×1400×1920mm
Net Weight	400 Kg

BS5540L TECHNICAL SPECIFICATIONS

Model	BS5540L
Voltage	380V/50HZ(3PH)
Power	27Kw
Conveyor Loading	80kg
Conveying Speed	0~10m/min
Tunnel Size	950×550×400mm
Overall Dimension	3100×850×1500mm
Net Weight	400kg