HOPAK HOPAK MACHINERY CO., LTD.

Servo Candy Packaging Machine C-TYPE



High speed candy packaging. Speed can up to 800 pack/min.

FEATURES:

- 4 independent servo motors with electronic control and 50 sets of recipe (bag length, temperature, speed, feeding position, film tension and cutting position) could reduce the initial lose of film and product for high efficiency.
- User-friendly human / machine interface control with 10.4inch colorful monitor.
- Self-diagnosis function, error message will show on screen for easy troubleshooting.
- Two layer of independent rotary disc (dia. 760 mm/60holes) with heating device is hygiene design(for easy clean)
- Three sets of feeding assistance brush and automatic Vibratory Chute for product feeding flow control, free of empty bag(or low empty bag rate), free of maintenance.
- Three sets of fin sealing rollers for high speed packaging.
- Optional different feeding systems (centrifuge rotary disc or stretching/cutting machine) are available for packing nougat, peanut brittle, Toffee...ect
- Optional auto splicer to increase productivity.
- Easily exchangeable sorting disc to accommodate other product size.

SPECIFICATION:

MODEL	HP-100C
Operating speed	300 - 800 pack/min
Bag length	50 - 75 mm (46 - 65 mm)
Max. film width	200 mm
(max. roll dia.)	
Product width (max.)	300 mm
Product Size	Width:15-33mm, Height:5-22mm
Machine Size	L:2640*W1500*H1590mm