

JY-350C-HSII Dual-Channel Ice Cream Automatic Packing Machine



Main performance & characteristics

1. The whole structure is in face-back-face pattern, easy to operate and convenient to maintain;
2. The whole structure is made of stainless steel, by special stainless steel surface treatment technologies and proper sealing technologies, completely rust-proof and water-proof, ideal for use in humid environment or other unfavorable environments for a long time;
3. Packing speed and packing length are controlled by perfect combination of advanced variable frequency speed regulation and servo driving technologies. The LCD screen is easy and convenient to operate;
4. Whole unit start and interlinked operating speed can be controlled by any one mainframe;
5. Packing length is tracked by photoelectric eyes accurately and automatically, manual adjustment is unnecessary after settings;
6. With features that the mechanism is precise and compact, and it is easy to operate, etc;
7. The unit can be used together with ice cream production lines to finish automatic materials feeding, transferring and packing in one time.

Using range

Ice-cream suit automatic production line can fit for one set of six, two sets of six, three sets of six auto-loading feeder, the yield is 7500 ~ 20000 / hour

Technical parameter

Packing speed (bag/minute)	125(1 Table)260(2 Table)335(3 Table)
Packing size (mm)	L180-238 W35-100 H20-40
Maximum width of film (mm)	350
Motor power	2.5KW(1 Table) 5KW(2 Table) 7.5KW(3 Table)
Heats up power	23.2KW(2 Table) 4.8KW(3 Table)
Rated voltage	220V
Rated frequency	40Hz
Weight of the machine	750kg(1 Table)1500kg(2 Table)2250kg(3 Table)