



## *Standard Drip Coffee Packing Machine KST-181*



### **Application:**

- ◆Coarse Coffee
- ◆Moderate Coffee
- ◆Fine Coffee

### **Features:**

- ◆OBLIQUE type SCREW FEEDER, No stuck, high accuracy and easy to adjust.
- ◆3-SIDE ULTRASONIC SEALING, makes better packaging performance.
- ◆Imported MITSUBISHI PLC, with WEINVIEW touch screen, easy operation.
- ◆Equipped with SAFETY GUARD DOOR, better protecting of machine, to provide the safety precautions for the workers as well.
- ◆With special design of OUTER AIR BLOWING SYSTEM, effectively avoided the problem of 'WRINKLE'.
- ◆Widely applications, such as drip coffee bag, rectangular nylon tea bag and non woven coffee Bag.

**Parameters:**

| <b>Model</b>       |                | <b>KST-181</b>  |
|--------------------|----------------|---|
| Working Speed      |                | 40 bags/min   |
| Sealing Method     | Inner parts    | 3-side ultrasonic sealing                                 |
|                    | Outer parts    | 3-side heating sealing                                    |
| Weighing System    |                | Auger   |
| Bag Size           | Inner drip bag | Standard drip coffee: 90 * 74mm                           |
|                    | Outer envelop  | 120 * 100mm( L *W )                                       |
| Packing Material   | Inner bag      | Nylon/Non woven/PET, any that can be sealed by ultrasonic |
|                    | Outer bag      | Laminated material(such as PE/PET/PP)                     |
| Bag Type           |                | Rectangular   |
| Weighing Arrange   |                | 8~15 grams/bag( based on the material's proportion)       |
| Air Consumption    |                | ≥0.6Mpa   |
| Power              |                | 220V Single phase 50/60Hz                                 |
| Weight             |                | 680KG   |
| Overall Dimensions |                | 1404 * 1080 * 2202mm( L * W * H )                         |