

Food Stretch Film Vacuum Packaging Machine SS-320V



It is a packaging machine that lays out the material, vacuum seals the film in the upper film area, and cuts it into a single product by cross-cutting and longitudinal cutting; because the stretch film packaging machine does not need to customize the bag in advance, but is covered by the bottom film and the upper film. Some users become laminating machine or four-side sealing packaging machine; the working principle of stretch film packaging machine is simple, no custom packaging bag is required, and there is no requirement for product packaging size.

Specification:

| Parameters/Model | SS-320 | SS-420 | SS-520 |
|------------------------|------------------------|------------------------|------------------------|
| Up film width | 293-294mm | 395mm | 492-496mm |
| Down film width | 322mm | 425mm | 520-525mm |
| Packing Speed | 5-8 cycles | 5-8 cycles | 4-7 cycles |
| Vacuum degree | ≤200Pa | ≤200Pa | ≤200Pa |
| Machine Dimension | 4800×850×1760mm | 6500×900×1700mm | 7000×1050×1860mm |
| Machine Weight | 1100kg | 1800 | 2400kg |
| Power | 3P, AC380V, 50Hz, 12KW | 3P, AC380V, 50Hz, 12KW | 3P, AC380V, 50Hz, 20KW |
| Compressed Air | 0.6-0.8Mpa | 0.6-0.8Mpa | 0.6-0.8Mpa |
| Pressure Cooling water | ≥0.15Mpa | ≥0.15Mpa | ≥0.15Mpa |