

Automatic Multi-head Weigher Granules Pouch Packing Machine CD Series



- Food:Candy,Beans,Chips,Popcorn,Pasta,Corn,Rice cake,Jelly,Cookies,Cheese,Peanuts,Coffee Creamer,Almond,etc.
- Daily necessities:Mothballs,Disposable Mask,Buttons,etc.
- Hard&Ware:O ring,Screw,Dowel,etc.
- Medical:Pill,Medicine,etc.

Features:

- Requirement for high precision measurement and fragile packaging bulk goods, such as: puffed food, crispy rice, fruit chips, sweets, pistachio, apple slices, dumpling, chocolate, balloon, rubber, Screw the Nut hardware item, medicines etc.
- Highly sensitive weighing sensor, with the highest measurement accuracy up to $+ / - 0.5g$.
- Anti-acid-base 304 stainless steel plate, meeting the standards of food SC certification and drug GMC.
- The standard procedure is to make sheet metal parts by hand. The mounting error is as small as 1mm

- Automatic bayonet weighing hopper, storage hopper, main vibration and wire vibration without screw fixation. Simple disassembly and convenient cleaning
- 10 sets of customized storage data, which can store 10 sets of commonly used parameters. When it is necessary to switch parameters, it is convenient and fast to switch with one key
- There are 50 kinds of basic parameters of products with different attributes and shapes in the database. Only the same or should be selected when weighing Similar material pictures, and then set the weight to complete the measurement part. Easy to understand.
- You can customize the concavo-convex pattern plate, rotary weight, no material storage, non-stick material. One said multi-purpose, can achieve the same type of product diversified packaging.

Technical Parameters:

Model	160CD	420CD	520CD
Film Roll Width	Max.320mm	Max.420mm	Max.520mm
Bag Length	Max.250mm	Max.300mm	Max.450mm
Bag Width	Max.150mm	Max.250mm	Max.250mm
Measuring Range	Max.500G	Max.1500G	Max.3000G
Packing Speed	20-80 bags/min		
Power	220V,50HZ,2KVA	220V,50HZ,2.2KVA	220V,50HZ,2.6KVA

Model	720CD	1050CD
Film Roll Width	Max.720mm	Max.1050mm
Bag Length	100-450mm	100-750mm
Bag Width	100-350mm	100-500mm
Measuring Range	Max.5000G	Max.15000G
Packing Speed	20-80 bags/min	
Power	220V,50HZ,3.6KVA	220V,50HZ,4.6KVA