



## *Twins Chamber Vacuum Machine DZ-400 2S*



When one chamber is working, another take packed items into another chamber. Thus you can save the filling time to make efficiency double.

### *Smart Digital Control Panel*

- Quick multi programs switch
- Panel mask Support customization
- Support manual sealing
- Accurate parameter control

### *Food-Grade Main Structure*

- Constructed of high-quality SUS304 stainless steel
- Use Switzerland laser cutting device to produce
- Smooth feeling by meticulous surface treatment
- Strong structure by finite element analysis
- Glossy chamber and beautiful brushed shell

### *Efficient Heat Dissipation*

- Powerful thermal fan
- As soon as turn off machine, fan will close
- Patent design for thermal holes
- Available eight consecutive hours working

### All Transparent Visual Lid

- Made of high-impact acrylic material
- Effortless designed hinges
- Durable sealing lid gasket by Special “V” sharped design

### Robust Sealing System

- Design patent for fastener of seal wire for add service life
- Double-seam is alternative
- Double-seam with cutting-off is alternative
- Two sealing bars is alternative
- Plug-in without cables sealing system is alternative

### Easily Maintaining Design

- Simple to open or close the shell
- Clear oil level viewing window
- Not difficult to replace the oil of vacuum pump
- Easy to displace wearing parts

### **Technical Specification**

<b>Model</b>	<b>DZ-400 2S</b>
Vacuum Pump Capacity	20 m <sup>3</sup> /h
Seal Length   S	430mm×2
Distance Between Seal Bar   B	390mm
Chamber Depth   D / D*1	90/140mm
Chamber Size	460×450mm
Distance From Floor To Platform   A	850mm
Power	1.5kW
Connection*2	230V/50Hz
Net Weight / Gross Weight	153/191kg
Dimensions   W x L x H (mm)	560×1050×925
Shipping Dimensions (mm)	630×1140×1105
Circle Time	3-4 times/min