

## *ZP37A Rotary Tablet Press*



ZP37A rotary tablet press is a new generation product which is developed from the former ZP37 Tablet Press and it's a continuously automatic rotary tablet press for pressing tablets, it is widely applicable to industries such as pharmaceutical, chemical, foodstuff and electron for pressing the granular materials into all kinds of round tablets, irregular tablets, two colors tablets and ring shaped tablets.

### **Features:**

- The machine is compatible with the GMP requirement, the outside part of the machine is fully enclosed, the material of the cover and the inside table face of the table-pressing room is stainless steel, the turret face has been disposed specially, nontoxic and smooth and abrasion proof.
- The machine has a greatly large power and pressure, and it has two pieces of prepressing tracks. It is stable in operation and is applicable to press hard-pressing powder.

- An overload protection unit is including in the system to avoid the damage of the apparatus, when overload occurs, the machine stops automatically, and at the same time the alarm light turns on.
- The speed adjustment of the driver is controlled by the frequency conversion device, it is easily to operated, safety and accurate.
- According to the special need of consumers, the function of communication network is to set equipment address and pass data in communication agreement criterion; it realizes higher-up managing equipment of work and output.
- The centralized lubrication system of the machine can ensure the oil supply to every lubricating part by the intellectual lubricating pump, and it is very reliable.
- To exert human nature ideas, the machine is easily to be cleaned and maintained.
- The transmission system is located inside the wormgear box under the main body, and it is a fully independent part. It cannot be cross-polluted, and the transmission system is fully lubricated so that the noise and the abrasion are greatly reduced.
- The ways to fix the lower track and lower pressure rollers are especial, so that be remounted and maintained conveniently and fast.

#### Technical Parameters:

Dies (sets)	37
Max. pressure (kN)	100
Max. dia. of tablet (mm) (Special shape longest side)	Φ14 (16)
Max. depth of fill (mm)	17
Max. thickness of tablet (mm)	8
Turret speed (r/min)	5-36
Max. production capacity (tablets/hour)	160000
Motor (kW)	5.5
Net weight (kg)	1800
Covering area (mm)	1100×940
Height including the hopper (mm)	1740
Height without the hopper(mm)	1500