

WF450 High Speed A reciprocating Packaging Machine



This machine is based on the common reciprocating pillow type packaging machine, which is controlled by full servo motor, improved structure, increased packaging speed, and added multiple detection and elimination, fault self diagnosis, alarm and shutdown, remote control and other functions, greatly improving the production efficiency, reducing personnel and production costs.

Features

1. Touch screen control is easy to operate.
2. The bag length can be selected at will, which can be adjusted automatically, quickly and accurately.
3. Reciprocating end sealing mechanism, servo motor drive, seal more firmly, no loss of sealing die cutter.
4. Aluminum plastic powder board servo feeding, one to five Board touch screen can be set arbitrarily.
5. The host machine is equipped with photoelectric color code tracking, and the benchmarking runs normally. In the process of operation, if the bag material joint pair plate is wrong and the synchronization fault occurs, the number of packages can be set to alarm and shut down.
6. PLC module, six groups of temperature control, temperature control, temperature setting display, on the touch screen.
7. Packaging film adhesive tape joint automatic detection weeding.
8. It can automatically detect and reject the missing code.
9. Drug plate missing version, multi version automatic detection and elimination.
10. Alarm and stop the machine for lack of film.
11. Menu memory function (can store various parameters of different packaging products).
12. Ethernet Remote control, can modify the program.

Technical Parameters

throughput	60-135bag/min
Film width	450mm
Cutting size	80-300mm
Product size	(Length)60-200mm, 寬Width)35-200mm, (Height)5-55mm
Weight	(about)1300kg
Voltage	AC220V/50Hz
Power	5.25kw
Dimensions	(L×W×H) 3750×1200×1700mm