

VY-60YP Plastic Tube Filling and Sealing Machine



With easy and quick adjustment, it is suitable for using multiple kinds of soft tubes for filling. The part contacting materials is made of 316L stainless steel, clean, sanitary and conforming to CMP for medicine manufacture.



- Compact design and auto tube feed. Driving part fully-closed.
- Tube washing and feeding marking identification, filling, folding, sealing, code printing and finished product output all conducted by a fully auto control system.
- Tube washing and feeding conducted pneumatically, accurate and reliable.
- Auto picket age affected by photoelectric inductance.
- Easy adjustment and dismantling

- Intelligent temp control and cooling system makes operation easy and sealing reliable.
- With easy and quick adjustment, it is suitable for using multiple kinds of soft tubes for filling.
- The part contacting materials is made of 316L stainless steel, clean, sanitary and conforming to CMP for medicine manufacture.
- With safety device, the machine is shut down when the door is opened and filling carried out only with tubes fed. Overload protection provided.

Technical Parameter:

Filling volume	1-250ml/unit (Adjustable)
Filling accuracy	$\leq \pm 1\%$
Capacity	1800-3600unit/hour, Adjustable
Tube diameter	$\Phi 10-50$ mm
Tube length	50-200mm
Hopper volume	40L
Power	380V/220V (Optional)
Air pressure	0.4-0.6 MPa
Equipped motor	1.1KW
Machine power	5kw
Inner wind motor	0.37kw
Convulsions motor	0.37kw
Dimension	1950×760×1850 (mm)
Weight	About 950 Kg