

Rotary Middle/High Speed Self-Adhesive Labeling Machine



Rotary labeling machine is applicable in wine'food, beverage, pharmaceuticals and daily chemicals etc.

It can stick square, flat, round, conic, double-conic, up-conic down-round, oval bottles, and has following labeling types, single labeling, double-labeling, sticking body-back-neck labels, round labels for the conic labels, three sides or four sides for square bottles etc.

Achieve the mechanical orienting through spot on the bottom and side. Also can go servo orienting through visual sensor detecting the LOGO or spue line, high accuracy, especially design for the highgrade products.

Using screw dividing bottle device, Star wheel directing plate feed bottles, and transfer the bottles to the center of platform so the labeling can be accuracy. Labeling station is different from the station of linear labeling machine. It can achieve 8 d adjustment, double pressing roller to provide labels so the labels can be tighten automatically, in the high speed the providing labels can be steady.

Equipped with many kinds of smoothing labels devices so guarantee the labeling accuracy and qualified conceding the transparent labels.

Bottle dia: ϕ 50-120mm

Bottle height:40-380mm

Main Technical parameters

贴标速度: 60-400瓶/分钟(与物料及标签尺寸有关) 贴标精度: ±0.5mm(不计物料及标签尺寸)

ф50-120mm

约2500kg 380V/50HZ 4.5kw

版度: 050-120mm 版高: 40-380mm 标签: 最大宽度300mm最大高度200mm 規格: 卷筒芯内径76mm 最大外径380mm 尺寸: L2400+W2200+H12000mm

Outline size:L2400*W2200*H12000mm Weight:about 2500kg Power supply:380V/50HZ 4.5kw

Labels roll dia:inner dia. 76mm, Max. 380mm

Production speed:60-400BPM(it is related to the material and dimension of labels)

Labeling tolerance:±0.5mm(Regardless of the package material error)

Wide range of labels: the Max width 300mm, the Max height 200mm