

Electric Heat Shrink Tunnel for Shrink Sleeves PM-1540S



Introduction:

1. This machine is a unique design for all kinds of bottles and cups. The label will be smooth without deformation after shrinking;
2. Multi axis type conveyor to ensure smooth conveying;
Imported components which makes sure the stability of the equipment;
3. These series of models use hot air circulation shrink systems, mainly for shrink label bottle-shaped, jars, cups etc. But also can shrink the bottle neck and cap
4. It is widely used in the bottle or cup body of beverages, pharmaceuticals, cosmetics, pesticides and other industries glass bottles, plastic bottles, cups and other containers.

Features:

- Stainless steel heater;
- High efficiency heat tunnel is thermostatically controlled up to 250 degrees;
- Hot air cycling tunnel with velocity control;
- Optional partial type air flow patterning for saving power;
- Work independently or in concert with production line.

Technical Parameter:

Model	PM-1540S
Power	3.5KW
Power Supply	3PH 220V/380 50/60Hz
Max Packing Size (Dia×H)	100×350mm
Tunnel Size L×W×H	1000×150×400mm
Packing Speed	20-40m/min
Applicable film	POF/PET/PVC
Machine Size L×W×H	1550×400×1460mm
G./N. Weight	270/250kgs