

Rotary Penicillin Bottle Filling And Riveting Machine XQZGM-1



Application:

1. It is widely used in precision, quantitative loading / dilution of pharmaceutical, pharmaceutical, food, chemical, cosmetic and other industries.
2. Pre-chromatography preparation, pharmaceutical QC and R&D, environmental monitoring, mineral and blood analysis, forensic identification.
3. Used for precise quantitative loading / dilution of blood, biological reagents, oral agents, injections, advanced cosmetics, flavors, fungicides and other liquids.

Characteristic

This equipment has been tested to meet the requirements of GMP certification.

1. The intelligent operating system is adopted.
2. The liquid filling part adopts high purity ceramic pump, which controls the injection volume of each lap by adjusting the angle of the pump head, and has extremely high measuring accuracy and repeated consistency.
3. 304 stainless steel appearance, desktop structure, practical and convenient.
4. Riveting part adopts special material coating hardening treatment, which has long service life.
5. The equipment is fast installed by mould, and it can be replaced conveniently between different bottle types.
6. This device adopts the German sensor to achieve the functions of no filling without bottle, no rivet cover without lids.

Technical parameters

Model	XQZGM-1				
Pump head	High purity ceramics				
Filling accuracy	$\leq \pm 0.4\%$				
Filling range	0.1-2ml	0.5-5ml	1-10ml	2-25ml	5-60ml
Manufacturing speed	0- 35PCS / minute				
Size of Host Machine	500*550*650(mm)				
Power	AC 220V 50-60Hz 550W				
Air supply	0.4-0.6Mpa				