



DPP-320A/250A/140A Blister Packing Machine



Features

1. The stroke of this aluminum blister packing machine is adjustable through inputting the sheet length on human interface.
2. The machine locates moulds through a locating notch; this makes it easy for mould replacement. And it heats the PVC through contacting and forms it through pressing and frothing.
3. PLC (Programmable Logic Controller) and step less frequency conversion adjustment.
4. The materials is fed automatically, the mould and feeder can be customized.
5. The cutter device, indentation device, batch number device and waste recovery device are all optional.
6. This aluminum blister packing machine adopts stepper motor traction and sprockets clamping operation which let synchronization more accurate and stable.
7. The heated moulds will automatically separate when the aluminum blister packing machine stops running to protect the materials and extend the service life of the machine.

Parameters

Model		320A	250A	160A
Blanking Frequency (times/min)		15 to 50	15 to 50	15 to 50
Sheet's Quality of One Blanking (sheets)		5 to 6	3 to 4	1 to 2
Producing Capacity (sheets/h)		5400 to 18000	3600 to 12000	1800 to 6000
Adjustable Scope of Feed Travel (mm)		10 to 150	10 to 140	10 to 130
Max Forming Area and Depth (mm)		320×130×13	250×120×13	140×110×13
Capacity of Air Compressor (m ³ /min)		≥0.45	≥0.38	≥0.36
Power Supply		380V 50Hz 12kW	380V 50Hz 8.5kW	380V 50Hz 6.5kW
Wapper Specification (mm)	PVC for Medicine	320×(0.2-0.5)	250×(0.2-0.5)	140×(0.2-0.5)
	PTP Aluminum Foil	320×(0.02-0.035)	250×(0.02-0.035)	140×(0.02-0.035)
Overall Dimension (mm)		3800×718×1750	3200×650×1450	2850×530×1450
Part Dimension (mm)		2000×718×1750	1750×650×1450	1450×550×1450
		1800×718×1750	1450×650×1450	1400×550×1450
Weight (kg)		2000	1700	1000