

Triple Servo Driven Horizontal Flow Packing Machine SH-500



Main Features:

1. PLC is combined with 7inch touch screen control system; it is easy to setup parameters. Product output and self-diagnostic machine error are directly showed on screen.
2. Triple Servo driven system, film speed is automatically synchronous with conveying speed.
3. When bag length is changed, the speed of transverse seal can be directly adjusted by hand wheel.
4. Machine design for easy maintenance and cleaning.
5. Pulling film wheel open is controlled by Pneumatic switch; the sealing wheel is automatically open when machine turn off.
6. It has safety guard to comply with CE standard.
7. Optional device: Photocell for printed film, Printer for date, line shaft for automatic feeders, etc.

Application: It is applicable for packing all kinds of solid and regular objects, including the foods such as biscuit, bread, instant noodle, ice cream, moon cake and soft sweets, and other objects such as toilet soap, medicated essence, note book, pen pack, tape and medicines in regular shapes.

Technical parameters:

Model:	SH-500
Speed:	maximum 250 pcs/min
Maximum film width:	500mm
Maximum film diameter:	350mm
Maximum packing height:	100mm
Maximum packing width:	200mm
Minimum package length:	76mm
Maximum package length:	564mm
Gas source:	6bar
Voltage:	380-400V 3ph
Power:	3.0kw