

TF6540A+BS5540L Mantle Sealing and Cutting Packing Machine



The plane introduction PLC and touching screen fully automatic computer control, and has no obstacle warning function. It is currently closed Reshousu packaging machine sets already more advanced packaging equipment. The aircraft mainly canned drinks, bottle-shaped sets out a whole block letters cut packaging, and with constant temperature (PE) by supporting the sue of stoves, packaging supplies reach integrity, a good contraction effects. And automatic production lines with more showing its superiority. The scope of application of machine, high economic efficiency, operational convenience. It is apply to PE film packaging materials, packaging cartons compared to traditional, much of the packaging cost savings.

F6540A TECHNICAL SPECIFICATIONS

Model	F6540A
Voltage	AC 220/50~60 V 110/50~60 Hz
Power	1.5 KW
Max. Packing Quantity	4×6 PCS
packing Speed	8 Pcs/min
Max. Sealing Length	650 mm
Working Air Pressure	6~8 Kgf/cm ²
Dimension (L×W×H)	2450×1750×1950 mm
Net Weight	350Kg

BS5540L TECHNICAL SPECIFICATIONS

Model	BS5540L
Voltage	380V/50HZ(3PH)
Power	27Kw
Conveyor Loading	80kg
Conveying Speed	0~10m/min
Tunnel Size	950×550×400mm
Overall Dimension	3100×850×1500mm
Net Weight	400kg