

## *BY8-200P Powder Pouch Filling and Sealing Machine*



This line mainly installs rotary packing machine and liquid filling machine, suitable for packing all kinds of liquid, such as fruit juice, hand sanitizer, liquid detergent and so on.

### **Main Features:**

- Wide range of pouches: All kinds of pre-made pouches such as flat and stand-up pouches.
- Easy to operate: PLC and color panel, fault indication on the panel.
- Easy to adjust: Needs 10 minutes to adjust clamp to suitable for different pouches.
- Frequency control: Speed can be adjusted by frequency conversion within the range.
- No pouch/incorrect pouch opening-no fill-no seal, machine alarm.
- Machine alarm and stop when the inadequate air pressure.
- Hygienic construction, the product contact parts are adopted sus304 stainless steel.
- Imported engineering plastic bearings, no need to oil, and no contamination.
- Oil-free vacuum pump, avoid the pollution of the production environmental.

**Technical Parameters:**

<b>Model</b>	<b>BY8-200</b>
Packing Speed	22-45 bags/min (Depended on the product and filling weight)
Bag Size	W: 70-200mm L: 100-300mm
Bag Types	All kinds of compound bags, such as flat bag, 3-side sealing bag, 4-side sealing bag, zipper bag, standup bag etc...
Filling Range	5-2000ML
Total Power	2.6KW
Weight	1000kg
Model	Filling Machine Two heads
Filling Range	50-500ML
Filling Accuracy	Accurcy $\leq \pm 0.5\%$
Metering Mode	Airtac type
Filling Speed	20-40 time /min
Voltage	1 Phase 220V 50/60HZ
Air Pressure	0.4-0.6MPa