



## *High Speed Steam Shrink Tunnel DZBS1135*



### **Features**

1. Much More Solid Stainless Steel Structure Machine
2. 2.5mm-3mm thickness wall
3. Better Design and More Groups of adjustable Steam Spreading Nozzles ,adjustable for shrinking different position of label on container
4. Equipped with water and steam separator to make steam vaporous steam, make steam shrink application better and remaining tiny little steam on container after shrink
5. Excellent design inter layer for waist steam and Equipped with 6units of waste steam let out exit with volume valves controllable. Make sure every second the exhaust steam is gone clean by the blower fan on top.
6. Good chamber to always keep the steam shrink pressure
7. Big humanization door handle to open and close tunnel window

**Technical Parameter:**

<b>Model</b>	<b>DZBS1135</b>
	<b>steam shrink tunnel</b>
Voltage	220V 50/60HZ
Power	150w
Conveyor motor	AC120w
Conveyor speed	0-10m/min
Shrink tunnel	1000*100*320mm
Max packing size	φ80*290mm
Capacity	5000~7500B/H
Max loading	15kg
Steam Pressure	0.1Mpa
Steam Consumption	8Kg/H
Shrink Temperature	75~85°C
Machine size	1760*400*1250mm
Machine weight	68kg