

Automatic Reverse Film Packaging Machine KD-260A, KD-350A, KD-450A



It is suitable for more material blocks (Dates, olives, candy, betel nut, pasta), multiple packet soup, solid dispersing materials, small Electronic components of irregular objects.

Details:

1. Compact structure stable function and simple operation.
2. The first third-generation double frequency control of the bag could be set and cut, unnecessary adjust air without changing film color code, tracking one pace reaches the designated position, it's saving lime and film.
3. It adopts imported electric appliances, touch man-machine interface, convenient parameter setting.
4. Self-checking function, trouble can be read easily.
5. High sensor photoelectric color chart tracking, make the cutting position more correctly.
6. Dependant temperature PID controlling suitable for various materials of packaging membrane.
7. Position stop function, no adhesive, and no waste of membrane.
8. Clean rotation system. more reliable operation and more convenient maintenance.
9. All the controlling operates by the software, convenience for function adjustment and technical upgrading.

Technical Parameters:

| Model | KD-260A,KD-350A, KD-450A |
|-----------------------------|---|
| Max Film Width | 260mm, 350mm, 450mm |
| Bag Length | 60-200mm, 60-300mm, 80-400mm |
| Packing Width | 25-100mm,50-150mm, 50-200mm |
| Packing Height | 5-45mm, 5-50mm,10-80mm |
| Thickness of Film | 0.03-0.06mm |
| Max Packing Capacity | 40-250 times/minute(Its depend on different material) |
| Power | 220V 50HZ 2.4KW-2.7KW |
| Overall Dimension | 4100x950x1500mm,4100x1000x1500mm |
| Weight | 550kgs, 600kgs, 680kgs |

Automatic Reverse Film Packaging Machine KD-260A, KD-350A, KD-450A



It is suitable for more material blocks (Dates, olives, candy, betel nut, pasta), multiple packet soup, solid dispersing materials, small Electronic components of irregular objects.

Details:

1. Compact structure stable function and simple operation.
2. The first third-generation double frequency control of the bag could be set and cut, unnecessary adjust air without changing film color code, tracking one pace reaches the designated position, it's saving lime and film.
3. It adopts imported electric appliances, touch man-machine interface, convenient parameter setting.
4. Self-checking function, trouble can be read easily.
5. High sensor photoelectric color chart tracking, make the cutting position more correctly.
6. Dependant temperature PID controlling suitable for various materials of packaging membrane.
7. Position stop function, no adhesive, and no waste of membrane.
8. Clean rotation system. more reliable operation and more convenient maintenance.
9. All the controlling operates by the software, convenience for function adjustment and technical upgrading.

Technical Parameters:

| Model | KD-260A,KD-350A, KD-450A |
|-----------------------------|---|
| Max Film Width | 260mm, 350mm, 450mm |
| Bag Length | 60-200mm, 60-300mm, 80-400mm |
| Packing Width | 25-100mm,50-150mm, 50-200mm |
| Packing Height | 5-45mm, 5-50mm,10-80mm |
| Thickness of Film | 0.03-0.06mm |
| Max Packing Capacity | 40-250 times/minute(Its depend on different material) |
| Power | 220V 50HZ 2.4KW-2.7KW |
| Overall Dimension | 4100x950x1500mm,4100x1000x1500mm |
| Weight | 550kgs, 600kgs, 680kgs |

Automatic Reverse Film Packaging Machine KD-260A, KD-350A, KD-450A



It is suitable for more material blocks (Dates, olives, candy, betel nut, pasta), multiple packet soup, solid dispersing materials, small Electronic components of irregular objects.

Details:

1. Compact structure stable function and simple operation.
2. The first third-generation double frequency control of the bag could be set and cut, unnecessary adjust air without changing film color code, tracking one pace reaches the designated position, it's saving lime and film.
3. It adopts imported electric appliances, touch man-machine interface, convenient parameter setting.
4. Self-checking function, trouble can be read easily.
5. High sensor photoelectric color chart tracking, make the cutting position more correctly.
6. Dependant temperature PID controlling suitable for various materials of packaging membrane.
7. Position stop function, no adhesive, and no waste of membrane.
8. Clean rotation system. more reliable operation and more convenient maintenance.
9. All the controlling operates by the software, convenience for function adjustment and technical upgrading.

Technical Parameters:

| Model | KD-260A,KD-350A, KD-450A |
|-----------------------------|---|
| Max Film Width | 260mm, 350mm, 450mm |
| Bag Length | 60-200mm, 60-300mm, 80-400mm |
| Packing Width | 25-100mm,50-150mm, 50-200mm |
| Packing Height | 5-45mm, 5-50mm,10-80mm |
| Thickness of Film | 0.03-0.06mm |
| Max Packing Capacity | 40-250 times/minute(Its depend on different material) |
| Power | 220V 50HZ 2.4KW-2.7KW |
| Overall Dimension | 4100x950x1500mm,4100x1000x1500mm |
| Weight | 550kgs, 600kgs, 680kgs |