



Shrink Sleeve Label Applicator MULTIPACK-120



Shrink sleeve label applicator from Multipack is high speed labeler equipment destined with latest shrink technology. It is equipped with MMI and PLC features for convenient machine operation. Our engineers have designed the bray center and base of this machine so accurately that it can work with the same high-speed performance even when the production requirement is more. We have different models of shrink sleeve label applicators which consumers can choose based on its labeling capacity per minute. This device is used with varying labeling speed starting from 50 containers per minute to 200 containers per minute. Our shrink sleeve applicator can be easily modified to match the product shape. It is a flexible device for labeling different products irrespective of shape such as a cap or a bottle. Our labelling device is a universal labeling device applied in wide range of industries including pharmaceutical industry, food and soft drinks manufacturing companies, etc.

Apart from general machining features and specifications, this device from Multipack is complete automated in operation. It can easily adapt different labeling materials including shrink bands and tamper evident labels for complete body sleeve applications of all dimensions, etc. Above all, our applicator can change the labeling material stock into shrink band which in turn becomes compatible to roll and unroll during labeling operation. It can label 250 products per minute and it is one of the cost effective and fast performing secondary packaging equipments.

Feature

- We have strictly followed GMP norms while designing this device
- The whole structure of applicator and conveyor is made of SS 304 and the tunnel is made from MS and powder coated material.
- This feature supports for consistent product conveying It is completely vibration free and favors for flawless operation

Specifications:

MODEL	MULTIPACK-120
Voltage	220V/380V 50/60 HZ 3 PHASE
Bottle Diameter	Ø55~Ø95 / Ø95~Ø125
Max. Speed	Up to 120 Bottle per minute
Power	2.5KW
Label Insertion Length	300MM
Range Of Label Thickness	0.035~0.08MM
Material	PVC/PET/OPS
Shrink Tunnel Capacity	5KW~17.5KW