

Wet Glue Labelling Machines LABELSTIK-400



India's First, Automatic Super High Speed Vertical Rotary Sticker Labelling Machine Model LABELSTIK-400, is one of the most user friendly. The Machine incorporates latest sophisticated Micro Processor Control Label Dispensing system with user friendly Sensing system for Label and Product. The machine is suitable for Labelling on Glass Ampoules, Vials, and other Round Objects. It is capable of Labelling up to 400 units per minute depending on products and label size. Specially designed electronic and mechanical system to apply transparent (No Look) Labels on Ampoules and Vials at very high speed using optional special label sensing system.

LABELSTIK-400 Truly one and only High Speed Rotary Sticker Labelling Machine available in India, with unique single point synchronised speed control system. The Inbuilt Automated Label Length detection systems eliminates any need for manually feeding and storing of Label Length data in memory and retrieving the same every time for change of Label Size & re-starting the Machine. The System thus saves valuable time, avoiding machine-down time, and helps achieve higher production.

Machine with added advantages like Stainless Steel Wire Mesh Feeding belt for feeding Ampoules / Vials in Vertical Position directly from the Trays and Similarly collection of Labelled product in Trays, Operator can feed the Ampoules / Vials directly from the Tray Online without stoppage of Machine. The Feeder belt system effectively eliminate clumsy, inconvenient, time consuming and prone to breaking of Ampoules etc. at the time of Loading the products for Labelling compare to other Slant Hopper Product Feeding System.

Machine also available with optional Turn Table for Feeding of Vials for online transfer of Vials from Capping/Inspection machine to Labelling and online transfer of Labelled vial to packing conveyor/inspection system. This system helps for continues Labelling operation for vials.

Machine can be supplied with Optional Toughened (Tampered) Glass or Acrylic Safety Cabinet. Machines having required all basic features as a standard fitment to match the current market needs and also saves cost and time.

LABELSTIK-400 Model also available with Max. speed of 300 and 200 Ampoules / Vials per minute. We have another 600 Series Rotary Ampoule / Vial Labelling Machine having built in online Ampoule/Vial Ejection System.

Technical Specifications

Label Height	8 mm to 50/70/90 mm Standard*
Label Length	12 mm Standard*
Label Roll Dia.	400 mm
Core Dia.	75/76 mm
Gap Between two Labels	appx. 3 mm
Product Diameter	Up to 25 mm*
Electrical	220 VAC Single Phase Power Supply (50/60 Hz)
Power	2.5 Amp.
Capacity	0.75 Kw
Speed	LABELSTIK-400 Up to 400 Labels per minute LABELSTIK-400.300 Up to 300 Labels per minute, LABELSTIK-400.200 Up to 200 Labels per minute, Labelling Machine speed also depending on Product and Label Size
Product Feeding Belt height	850 mm*
Overall dimension	1800 mm(L) X 1400 mm(W) X 1100 mm (H)
	with T.G. Cabinet 1800 mm(L) X 1400 mm(W) X 1900 mm (H)
* Specification can be changed as per customers requirements	