

KX-W25 Horizontal Carton Opener/ Erector



Technical features:

- Adopt PLC+touch screen control to display the action status and alarm information in real time
- The unpacking speed can be adjusted at will (inverter control).
- Door opening safety protection function, the machine will pause and alarm when the door is opened
- Automatic warning reminder function for lack of cartons in the hopper.
- The carton storage adopts horizontal type, and empty cartons can be replenished at any time without stopping the machine. Alarm function for lack of tape.
- The whole machine adopts cam continuous system and precise mechanical operation.
- It is equipped with full box detection function, and the machine will automatically pause when the cartons are piled up on the back-end assembly line.
- Other options:
 - ① Specified brand of electrical components
 - ② Stainless steel body/customized color
 - ③ Can be equipped with hot melt adhesive sealing
 - ④ Can customize non-standard size equipment.

Equipment parameters:

Model	KX-W25
Power supply	220V 50HZ 750W
Applicable carton	$L+W \leq 900\text{mm}$; $W \leq 400\text{mm}$; $H+1/2W \leq 530\text{mm}$; $1/2W \leq 200\text{mm}$
Speed	$\leq 25\text{Box/minute}$
Air pressure	$\geq 6\text{Kg/cm}^2$
gas consumption	$0.45\text{m}^3/\text{min}$
Tape	W48~75mm * L900码 Paper core $\phi 75\text{mm}$
Tie length	50~70mm
Carton storage	Horizontal box storage, box rack height 800mm
Table height	900-950mm
Mechanical Dimensions	L2450*W1150*H1800mm
Mechanical weight	990Kg