

TY-7112 Automatic L Sealer



Machine features

- Apply Mitsubishi PLC controller for stable operation performance.
- Apply Omron timer for control sealing & cutting time.
- Individual pin roller, enable to adjust pin position & amounts according to request.
- Adjustable film filling tension.
- Product entry height and width are adjustable directly without hand tool.
- Panasonic sensors for product entry reading.
- Cutting blade made by 1 piece with long time operation durability.
- Temp. controller with PID function and driven by SSR for stable heating performance.
- Auto abnormal warning on sealing & cutting device.
- Infeed conveyor apply with roller enhance smooth operation.
- Rubber roller for tight film holding with timing belt pulling.
- Film collection device can be easily install / dismantle without hand tool.
- Customized machine with product delivery, stacking, and sealing to cutting is available upon request.
- CE model available
- Please refer shrink tunnel according to product size for shrinking application.
- 5-6 kg/cm² filter air is self-prepared by buyer.

Specifications

Model	TY-7112
Machine(mm) L x W x H	2100 x 930 x 1580mm
Package Range(mm) L x W x H	L:100-500mm
	W:60-330mm
	H:5-120mm
Speed	1-25 packs/min
Air consumption	120L/min
Power supply	220V/60Hz/1 phase(upon request)
Power consumption	2.6KW
*Other packaging size available upon request.	
*The speed will be differ from product size, film thickness & operator.	
*One option on max. product length, width or height while packaging.	
Optional Device/Function:	
Closing conveyor(for small product)、anti-cut protection、3 in 1 blade(for PE film)、adjustable sealing height、sealing line position、S/S machine frame...etc., other requirement available upon request.	