



SH-GYCR4A Automatic Servo Magnetic Gear Pump Chemical Bleach Detergent Acids Corrosive Liquid Filling Machine



Main Feature

- ▶ Designed for filling corrosive liquids like bleach, disinfectants, toilet cleaners, detergents & acids, etc.
- ▶ Servo-driven magnetic gear pump controls filling, ensuring filling precision and stability. Quantity of filling nozzles can be customized according to your production needs.
- ▶ Built with PP structure and fluororubber hoses for long-term durability.
- ▶ With anti-dripping filling nozzles, effectively preventing leakage and maintaining cleanliness.

Parameter

- Machine Model: SH-GYCR4A
- Voltage / Power: 110V / 220V, 50–60 Hz, 5000 W
- Air Pressure Requirement: 0.4–0.7 MPa
- Suitable Bottle Diameter: $\phi 50$ – $\phi 110$ mm
- Suitable Bottle Height: 60–300 mm
- Hopper Capacity: About 120 L
- Recommend Filling Range: 300 ml – 10L
- Max Flow Rate: 27L/min
- Filling Material Temperature Range: Room Temperature(Customizable for high-temperature materials)
- Filling Material Viscosity: 0-1000cps(Customizable for higher viscosity)
- Filling Speed: 200–2500 BPH (based on filling volume)
- Machine Size: About 2000 × 1300 × 1900 mm (L×W×H)
- Machine Weight: About 280 kg