

Kawach Servo

With Servo Auger Filler

*It's stronger
It's Faster
It's Economical
It just works works & works...
Without tiring*



The machine is best for...

Free flowing powders like Haldi, Mehendi, Besan, Flour, Talcum Powder, Ground Spices, Herbal Powder, Soluble Fertilizer Powder and all kind of Fine Powders.

KAWACH Servo Machines are very high speed machines of international standards with all precision. The high end CPU motion control Technology gives the highest speed upto 120 pouches/min. (Depend on product material characteristic & pouch size). All operations are handled by individual servo motor.

Kawach servo machines are designed only for large scale manufacturer. These machines runs at high speed with high weight accuracy & sealing intactness.

These machines are controlled by motion CPU with touch Screen.

These machines have many unique features. Servo Driven Auger Filler is for precise weight accuracy at high speed.

Additional Systems

Online batch coding device.

Inert gas flushing system.

3 side, 4 side, center sealing, Guzzeting, block bottom, etc.(optional).

Batch cutting device.

No material machine stop.

No Film machine stop.

Static charge eliminator for dust free sealing.

Available in GMP model for Pharmaceutical users.

'D' cut or Euro slot or any shape which made to carry the bags easily.

The Perfect Way To Pack

Kawach Servo

With Servo Auger Filler

SPECIFICATIONS

Filling capacity (Range)	1 gm to 5 kg
Output speed	35 to 120 pouches/min (Depend on material characteristic, fill weight & pouch size)
Control	CPU Motion Controlled
Operation	Servo driven
Packaging Material	Laminated film
Heating System	Hot bar induction heating
Reel Core Diameter	70 to 76 mm
Roll Holding	Pneumatic shaft
Maximum Roll weight	60 kg
Electricity required	420V, 3Ph, 50Hz
Compressed Air required	2 cfm at 6 bar pressure
Machines Weight (Approximate)	700 kg to 1500 kg
Dimension (Approximate)	1000 (w) X 1200 (b) X 2850 (h) mm
Available in variety of Models	1gm - 5gm, 1gm - 10gm, 1gm - 19gm, 1gm - 25gm, 5gm - 50gm, 10gm - 50gm, 20gm - 100gm, 50gm - 250gm, 100gm - 500gm, 200gm - 1kg, 500gm - 2kg, 1kg - 5kg.

Note : The design / specification are subject to change without notice on account of continuous improvement in product quality.

Unique & Special Features

- High end CPU motion control with touch Screen.
- Individual Servo Motor for each operation.
- Computer, printer & Internet connectivity.
- Recepte function on touch panel.
- Built in self fault diagnosis system.
- Three level password protection for settings.
- Auto Web tracking device.
- Integrated PID temperature Controlled for precise temperature control.
- Very low maintenance (Almost maintenance free).
- If 'No material or no film' machine stop.
- Batch cutting device (Optional)
- All contact parts in SS-304. SS-316L on request.
- Epoxy powder coated structure.
- Weight adjustment & speed variation through Touch screen.
- High density heaters for long life & minimum warm up time.
- Three sensor controlled film unwinding device.
- Operational & maintenance manual in touch screen.



Saurabh

Flexipack Systems Pvt. Ltd.

Manufacturer of Flexible Packaging Machinery & Allied Systems

Regd. Office & Factory: Plot No. 6 & 17, Gat No. 1556 / 1559,
Dehu - Alandi Road, Shelarwasti, Chikhali, Tal. Haveli, Pune - 412 114
Ph.: +91-20-27492722; 66346900, Fax.: 66346904.

Email: saurabhpackaging@hotmail.com; sales@saurabhflexipack.com
website : www.saurabhflexipack.com

Branches : Mumbai, Ahmedabad, Rajasthan, Chennai, Hyderabad, Bangalore, Kolkata, Delhi