



## *Vertical Form Fill Sealing Machine AP-1200L*



This model is facilitated with various sides sealing, which guarantees complete safety. This is designed for fast and easy changeover and thus packaging is done fastly. Electronic web edge control with excellent sensitivity and high precision is installed in this model and closely monitors and controls the wind and unwinding of the bags keeping an edge in the correct position.

### **Salient Features:**

- Sturdy construction as these are manufactured with stainless steel
- PLC or servo controlled
- Operating panels are easy to use
- Fast and easy changeover
- Requires low maintenance and service

**Technical Specifications:**

<b>Machine speed</b>	Up to 90 SPM depending on the product & sachet/pouch dimension.
<b>Packing range</b>	Suitable to pack up to 200 ml and depending upon product to be packed
<b>No. of tracks</b>	Up to 16 tracks depending on sachet/pouch width
<b>Max. roll width</b>	1200 mm
<b>Max. roll dia</b>	500 mm
<b>Max length of pouch</b>	Up to 220mm
<b>Film draw mechanism</b>	<b>Options</b>
	a) Servo based
	b) Electromagnetic clutch and break
<b>Web controller</b>	<b>Options</b>
	a.)Electronic web edge control
<b>Compressed air</b>	4 CFM @ 6 kg/cm sq
<b>Electrical power required</b>	Up to 12 KW
<b>Main Body Frame</b>	<b>Option</b>
	- MS with Powder coating.
	- MS with SS cladding
<b>Type of Sealing</b>	Side Sealing
<b>Machine dimension</b>	3090 mm X 3375 mm X 2300
	(Height mm X Width mm X Length mm)
<b>Net Weight</b>	3500 kg