

Flat Bottle Labeling Machine JS-1530F



Joysun JS-1530F model flat surface labeler is designed for flat objects including flat bottles, square bottles, carton surfaces, paper surfaces, can cap labeling and top labeling. It is widely used in after-packaging lines. It can be connected to the packaging line with an unscrambler machine at the head and inspection machine behind.

Functions:

- ① Hot coding/printing function (production date, product batch number, expiration date);
- ② Automatic feeding function (considering product consideration);
- ③ Automatic receiving function (considering product consideration);

Label Requirements:

- 1. The interval between the labels is 2-4mm;
- 2. The label is 2mm away from the edge of the bottom paper;
- 3. The bottom paper of the label uses glassine base paper, which has good toughness to prevent breaking;
- 4. The inner diameter of the core is 76mm, and the outer diameter is less than 280mm.

Characteristics:

- 1. The card, paper is stable and the card is sorted with advanced sorting technology. The sorting rate is much higher than the regular ones.
- 2. Card labeling speed is high, for example, the supervision code for the medicine box can be stabilized at more than 150 pieces/minute;
- 3. Wide range of applications, can be used to label a variety of cards, paper, and other items, suitable for unfolded carton labeling;

4. The labeling accuracy is stable. The pressing roller is used to press the workpiece, and the conveying is stable, and it can not be warped to ensure the labeling accuracy.
5. The structured combination of mechanical adjustment part and the clever design of label winding, labeling position are easy to fine-tune, which makes the conversion between different products and label winding easy and time-saving;

Parameter:

Model	JSL-1530F
Voltage	AC220V/50/60HZ/Single phase
Power	0.75KW
Label type	Sticker, transparent or opaque
Labeling speed	0-150 pieces per minute, upon label length
Position Accuracy	±0.5mm (not including bottle and label own accuracy)
Conveyor direction	from Left to Right; or Right to Left; can be connected to the packing line
Suitable Objects	Length: 25-150mm, width:10-12mm, Height 0-150mm
Suitable Label	Length: 25-100mm, Width: 20-90mm
Max. label roll	OD: 360mm, ID 76mm
Machine dimension	1600 (L) 500 (W) 1550 (H) mm
Net Weight	300kg
Optional	For special labeling and special size or container, customization is available