

PZH-100B Automatic Cartoning Machine



This model is suitable for automatic feeding and cartoning of bag-like items such as granule bag, soft double aluminum, plaster, band-aid, mask, coffee bag and so on.

The machine finished running by a series of photo-electrical controller to make the machine stability and guarantee the packing quality. It includes 1to 4folds leaflet automatic folding, cantons in suction and open, products and leaflet put into, printing batch number, sealing or option hot-glue device. The machine can be single used or linked, Shrink Machine, Three Dimensional Packaging Machine to form a production chain.

Feature:

1. Adopt international famous brand PLC automatic control system and frequency control.
2. Adopt human-machine interface operating system.
3. The main drive has an overload protection device.
4. Fault display, alarm and finished product count.
5. Stable performance and easy replacement of different product specifications.
6. Automatically remove the carton that lacks packaging and instructions.

Technical Data:

Encasing speed	50-100box/min.	
Box	Quality requirement	250-350g/m ² (According to its dimension to confirm)
	Dimension range (LxWxH)	(70-180)mm x (35-85)mm x (14-50)mm
Leaflet	Quality requirement	60-70g/m ²
	Unfold leaflet specification	(80-250)mm x (90-170)mm
	Fold range	(1-4) fold
Compressed air	Working pressure	≥0.6Mpa
	Air Consumption	20m ³ /h
Power supply	220V 50Hz	
Motor power	0.75kW	
Machine dimension (LxWxH)	3100 x 1100 x 1550mm	
Machine Weight	1700kg	