

Automatic Stick Powder Packing Machine HY-YBF50



It is suitable for automatic packaging of powder products with poor fluidity in food, health care and pharmaceutical industries, such as: freeze-dried powder, protein powder, gastrodia powder, pueraria powder, stone meal powder, notoginseng powder, whole grain powder, meal replacement powder, milkshake powder, ganoderma powder, bear bile powder, milk powder, coffee powder, solid beverage, etc.

Features

1. Adopt German Siemens PLC controller, color touch screen operation, Taiwan AIRTAC cylinder; France Schneider switching power supply.
2. Full pneumatic control, simple operation, less wear parts in the later stage, reducing parts replacement.
3. Material: The contact part of the box and material is made of SUS304 stainless steel, which meets GMP production standards.
4. The heat-generating parts and moving parts are hidden in the protective cover, which is safe and reliable.
5. The equipment is equipped with casters for easy handling and movement.

Characteristics

1. Long strip design, the capacity can be large or small, by setting the bag length value, can achieve different weight, reduce mold replacement.
2. Rounded shaped sachet, can design the size of the nozzle, tear horizontally to prevent the material from spilling; the arc corner can also prevent children from scratching Eye corners, increasing product safety.

3. Increase the vibration device to prevent the dust accumulation molding device from falling into the material feeding port, affecting the filling accuracy of the machine; at the same time, seal the material feeding hole through the food grade silica gel sheet to reduce the dust.
4. Punching die adopts HKS-9 material, after six processing techniques, high durability and long service life.
5. The equipment is easy to operate, and one ordinary female worker can see 3 sets of equipment.

Specification

Model	HY-YBF50
Filling Range	1-100ml
Sachet Size	W: 25-100mm, L: 30-180mm
Max. Film Width	220mm
Sachet Type	Round corner sitck
Filling Method	Pump
Capacity	20-45ppm
Power Voltage and Consumption	220V50-60HZ/2.0KW
Air Pressure and Consumption	0.3m ³ /min 0.6-0.8Mpa
Dimension (L*W*H)	670*850*1655mm
Weight	300KG
Packaging Film Materials	PE laminated film, such as PET/AL/PE, PET/PE, Nylon/PE, etc.
	Thickness: 0.08~0.12mm (3 or 4 layers)
	Inner Core Diameter: 75mm
	Outer Roll Diameter: 300mm