

Automatic Twelve Head Ropp Screw Capping Machine PARCS-240



Automatic ROPP Cap Sealing Machine is versatile, self-supported on stainless steel leg with height adjustable adjustment system. The machine is precision built on sturdy welded MS frame completely enclose in stainless steel sheet and doors are providing to facilitate the servicing of machine.

Operation:

The feed container moving on conveyor belt are fed into an infeed star wheel through In-feed worm, star wheel bringing the container below the sealing head in the subsequent indexing part, meanwhile the bottle pick up a cap from the delivery chute of cap filling bowl, where the body and the neck of the container are positioned below the rotating head, where the sealing head is performing perfect operation of threading & sealing.

Technical Specification:

Model		PARCS-240
Output/Hour*		4000 to 12000 bottles
Direction of Movement		Left to Right
No. of Sealing Head		12 Nos.
Electrical Specification**	Main Motor	2 HP / 415 Volts / 50 Hz
	Cap Feeding Bowl	0.25 HP / 415 Volts / 50 Hz.
Height of Conveyor**		860 mm to 910 mm.
Machine Dimensions**		2135 mm (L) x 1200 mm (W) x 2250 (H) Approx
Case Dimensions		2650 mm (L) x 1320 mm (W) x 2250 (H) Approx
Net Weight		1200 Kgs. Approx.
Gross Weight		1550 Kgs. Approx.
Change parts required		(A) Container: Star Wheel, Center Guide, Feed Worm
		(B) Cap: Die, Delivery Chute, Bowl