

KD-450 High-speed Tri-Servo Packing Machine



Applications:

Applicable for packing various solid regular objects, such as moonquake, bread, biscuits, candies, snow cakes, custard cakes, chocolates, instant noodles, medicines, commodities, hardwires, carton, trays and etc.

Technical Advantages:

- Programmed and controlled by 3 servo motors, the working speed regulated individually and the wrap bags length adjustable to meet different needs;
- User friendly Touch Screen HMI guarantee the easy operation and multi-language display conversion; Simple to operate and adjust settings through graphic HMI
- High-precision photocell control tracking system to recognize products with different colors and guarantee the precise sealing and perfect printing
- Easy format changes for packaging various sized products using adjustable former and ensures high production;
- Built-in heated Sealing Roller improves the speed and sealing reliability, avoids melting the film and cost-saving of package material;
- Double film roll spindles with automatic film splicer

Technical Data:

Model	KD-450
Film width	Max 450mm
Bag length	35-1000mm
Bag width	35-140mm
Product height	5-55mm
Film roll diameter	Max 350mm
Packaging speed	50-500 packs/min
Packaging materials	OPP, PVC, OPP/CPP, PT/PE, KOP/CPP, ALU-FILM
Power Supply	220V / 50/60Hz / 4.0KW
Machine size	(L)3910×(W)820×(H)1520
Net Weight	1500 KGS