

Horizontal Wrappers for Solid Single Piece Package



Features:

- *Horizontal packing wrappers are controlled by double frequency converters , step motor or servo motor to control the length cut in high accuracy without regulating empty running, saving time and film;
- *Adopt computer PLC control system, easy parameter set-up and self analyze;
- *High sensitive photocell chasing the bag length in high accuracy;
- *Independent PID control to suit different kinds of packing film;
- *Stop and position in accuracy, nonstick cutter, saving film; Easy transmission system, much stable and easy maintain.

Application:

Candy, pie (choose to equip with nitrogen gas generator or alcohol pure), soap, biscuit, bread, moon-cake, fast noodle, commodity, industrial parts, and different kinds of regular shape products with or without holding tray.

Model	D-320	D-350(X)	D-400	D-450(X/W)	D-600(X/W)
Capacity	40-230bags/min		30-180bags/min	20-80bags/min	
Bag size	W50-160mm L65-330mm	W50-160mm L30-160mm	W50-180mm L130-400mm	W50-160mm L120-450mm	W50-200mm L120-450mm
Product height	Max40mm	Max40-60mm		10-80mm	
Film roller width	Max320mm	Max350mm	Max400mm	Max450mm	Max600mm
(Film roller diameter) : Max320mm					
Machine packing dimension	L3770*W720 *H1450mm	L4020*W770 *H1450mm	L4020*W800 *H1450mm	L4380*W870 *H1500mm	L4380*W970 *H1500mm
Power supply	220V 50/60Hz 2.6KW		220V 50/60Hz 3.2KW		220V 50/60Hz 3.6KW
Machine weight	900kg		960kg		