

BY8-200S Granule Pouch Filling And Sealing Machine



This line mainly installs rotary packing machine and liquid filling machine, suitable for packing all kinds of liquid, such as fruit juice, hand sanitizer, liquid detergent and so on.

Main Features:

- Wide range of pouches: All kinds of pre-made pouches such as flat and stand-up pouches.
- Easy to operate: PLC and color panel, fault indication on the panel.
- Easy to adjust: Needs 10 minutes to adjust clamp to suitable for different pouches.
- Frequency control: Speed can be adjusted by frequency conversion within the range.
- No pouch/incorrect pouch opening-no fill-no seal, machine alarm.
- Machine alarm and stop when the inadequate air pressure.
- Hygienic construction, the product contact parts are adopted sus304 stainless steel.
- Imported engineering plastic bearings, no need to oil, no contamination.
- Oil-free vacuum pump, avoid the pollution of the production environmental.

Technical Parameters:

Model	BY8-200
Packing Speed	22-45 bags/min (Depended on the product and filling weight)
Bag Size	W: 70-200mm L: 100-300mm
Bag Types	All kinds of compound bags, such as flat bag, 3-side sealing bag,
	4-side sealing bag, zipper bag, standup bag etc...
Filling Range	5-2000ML
Total Power	2.6KW
Weight	1000kg
Model	Filling Machine Two heads
Filling Range	50-500ML
Filling Accuracy	Accuracy $\leq \pm 0.5\%$
Metering Mode	Airtac type
Filling Speed	20-40 time /min
Voltage	1 Phase 220V 50/60HZ
Air Pressure	0.4-0.6MPa