

Premade Pouch Filling Machine TH-PM-200/260/300



The premade pouch filling machine is suitable for all type of heat seal performed side seal bags, block bottom bags, zip-lock reclose able bags, stand-up pouch with or without spout, paper bags etc. It's a very popular packing solution for the premade bag packing.

The machine working process:

- 1. Bag feeder
- 2. PLC control system
- 3. Bag opening device
- 4. Unloading system
- 5. Cleaning system
- 6. Heat sealing system
- 7. Output system

Features:

1) Powder filling head use the Schneider servo motor, filling accurate and fast

2) The powder filling device use the touch screen, you can set the filling quantity and speed

3) Automatic rotary packing machine adopt precision indexing device and Siemens PLC to control each action and working station to make sure the machine operates easily and does accurately.4) The speed of this machine is adjusted by frequency conversion with the range, and the actual speed depends on type of products and pouch.

5) The machine has the safety system, no bag feeding, no filling and no sealing, no filling and no sealing

6) The premade pouch filling Machine body has the Waterproof device, it's easy to clean and wash

Technical Parameter:

| Model | TH-PM-200 | TH-PM-260 | TH-PM-300 |
|-------------------------|---|---------------------|---------------------|
| Filling capacity | 50g - 1000g | 50g - 2000g | 50g - 3000g |
| Packing bag width | 100-200mm | 100-260mm | 100-300mm |
| Packing bag length | 100-300mm | 100-300mm | 100-400mm |
| Filling speed | 20-60bags/min | 20-60bags/min | 20-60bags/min |
| Filling weight accuracy | ≥99.5% | ≥99.5% | ≥99.5% |
| Power supply | 4.5kw, AC220V, 50Hz | 4.5kw, AC220V, 50Hz | 4.5kw, AC220V, 50Hz |
| Machine weight | 920kg | 950kg | 980KGS |
| Application | Stand-up pouch, handbags, zipper bags, four-side sealing bags, three-side sealing bags, paper bags and other composite bags | | |