

## Fully-Auto Sleeve Type+Shrink Tunnel CE-6030AZ



### Features:

- Photoelectric switch, automatically sensing the length of the packaging.
- Adopt imported cylinder, make the pushing cutting more smoothly.
- Sealing system installed anti-cutting protection device to increase equipment safety.
- Sealing knife uses the aluminum knife with DuPont Teflon which is anti-stick coating & anti-high temperature. So the sealing will not have cracking, coking smoking with zero pollution.
- Use imported electrical components, reduce the failure in using.
- Packaging different shape specification products, the front positioning frame can be adjusted.
- Automatic manual can switch at any time.

### Technical Parameter:

Model	CE-6030/AZ	CE-6040/E
Power	2kw	18kw
Power Supply	AC220V 1/3 PH 50/60Hz	AC220V/380 3 PH 50/60Hz
Max Packing Size L×W×H	L(unlimited)×500×300mm	W500×H350mm
Tunnel Size L×W×H	/	1800×600×400mm
Blade Length	670mm	/
Air Temperature	0-300°C	0-300°C
Table Height	820±50mm	820±50mm
Packing Speed	25m/min.	0-25m/min
External Air Source	6-8kg/cm <sup>2</sup>	/
Shrink Film	PE	PE
Machine Size L×W×H	950×950×1865mm	2800×950×1750mm
Packaging Size L×W×H	1000×1000×2015mm	2850×1000×1900mm
G./N. Weight	420/380kgs	625/565kgs