

## *YS-BS-3620-CP Vertical Packaging Machine*



- The back sealed series machine are very popular. The continuous motion vertical machine designed for packaging a large variety of products at high speeds. Continuous pull film movement, Simple structure, Economical and practical
- Continuous motion leads to high productivity
- Lean machine concept enables cost-effective production
- Maintenance-free servo-technology ensures reliable production
- PLC controls enable precise machine movements for smooth production and good bag quality
- Intuitive HMI allows easy operation and short training time
- Open machine concept for easy access and maintenance
- Compact machine design for good ergonomics, product-conserving filling and saving space

### **Technical Parameters**

Model	YS-BS-3620-CP-A	YS-BS-3620-CP-P	YS-BS-3620-CP-GB
Bag type	1 .Pillow bag	Only pillow bag	Gusseted bag+
	2. Gusseted bag		bottom block
Standard capacity	10-110 bags/min	10-130 bags/min	10-100 bags/min
Size of pillow bag	Width : 60-360mm	Width : 60-360mm	Width : 60-360mm
Max size: 4.5L	Length: 60-500mm	Length:60-500mm	Length:60-500mm
Size of Gusseted bag	Width : 50-330mm		Width : 50-330mm
Width>2 times side depth	Depth : 45-140mm		Depth : 45-140mm
	Length: 60-500mm		Length: 60-500mm
Film parameter	packaging material:OPP/AL/PE, PET/VMPET etc.		
	Film diameter: ≤600mm		

	Core diameter:76mm
Total power	5 KW
Air pressure	≥0.5MPa
Air consumption	HS closure, 0.32NL/cycle
Outer dimensions (appr.)	2000*1500*2060mm
Weight (appr.)	780kg
Power supply (optional)	3N-PN-50Hz 380V/220V (3P 5 wires)