



CS-503 Semi-Auto Coverless Induction Cap Sealer



Specially designed for uncapped bottles, it's suitable for small enterprises, manufactories or labs for sealing various vessels in small quantities; it is light in weight, high in efficiency and easy to operate. It is used for sealing various types of bottles. We can customize different diameter's bottle. This machine does not contain air compressors, and must be self-prepared with an air pressure of 5 kg/cm² or more.

Features

1. Can be sealed without a cap
2. Highly efficient sealing function, capable of complete sealing in spite of small quantity of water, oil stains or powders on the bottle opening.
3. The device is designed to be simple and adjustable to suit vessels of various sizes and heights.
4. The device adopts imported solid power crystal assembly and the modulated design, which ensure low failure rate, convenient maintenance and low energy consumption.
5. The power and control cables adopt quick jacks, which allow easy assembly and disassembly.
6. Adopting IGBT/MOS-FET modulated design, the device is provided with low failure rate, reduced loss rate and doubled efficiency.
7. Sealing of vessels with different height can be achieved by adjusting the inductor.

SPECIFICATIONS

| MODEL | CS-503W |
|----------------|------------------|
| Power Output | 500W |
| Input Voltage | 110V或220V/1ph |
| Max. Current | 6A/3A |
| Cap Diameter | 15~120mm |
| Sensor | Air Cooled |
| Generator Type | IGBT |
| Frequency(KHZ) | 30-60K/Hz |
| Machine Size | 550*420*700 / mm |
| N.W. | 400*220*245/mm |
| Generator Size | 40 Kg |