

Capping Machines CAPSEAL-120



The Automatic Four Head Rotary Vial Capping Machine Model CAPSEAL-120 for PP/Flip-Off Aluminium Cap. Machine is suitable for Round Vials with maximum speed of 120 Vials per minute depending on Vial Diameter, Vial Height and Cap Size. Specially Machine construction in Stainless Steel finish including machine M.S. frame structure with Stainless Steel Cladding/Enclosures. Machine can be used for Molded or Tubular Glass Vials having Plain Aluminium Seals as well as Flip-Off Seals with common change parts for both type of cap.

Machine with Unique Single Roller Sealing System ensures perfect sealing of vials with lower setting time. The Machine is equipped with Vibratory Bowl Feeder for continuous feeding of Cap for online operation on any liquid or powder filling line. Machine suitable for various sizes of Vials as well as Plain / Flipp-Off Cap with the help of change parts. Capping Machine is suitable for application in Pharmaceutical and other industries requiring higher production speed on automatic online operation.

Features:

- No Vial - No Cap System
- No Cap - Machine Stop System
- Machine construction in Stainless Steel Finish
- In-feed and Exit Star Wheel with Overload Clutch System to avoid Bottle breakage
- Single Drive Synchronizing Total Operation of Star Wheel and Turret with Star Wheel
- Cap Feeder with Variable Speed System for feeding control of caps.
- Minimum Change Over and Setting time
- Spring Loaded Unique Free Spinning Single Sealing Roller
- Hopper can be completely dismantle for easy cleaning
- Various safety features including Clutch system to avoid Bottle Breakage
- Single Drive synchronizing operation of Conveyor and Star Wheel
- Minimum Change over time

Technical Specifications:

Vial Diameter	Up to 45mm*
Vial Height	75mm* Maximum
Aluminium / Flip-Off Cap Size	Applicable for 13mm, 20mm, 32mm or 38mm*
Electrical	415VAC 3Phase and 220 VAC Single Phase Power Supply (50 Hz) with A.C. Drive
Power	2.0 Hp
Conveyor Height	800-850 mm
Overall Dimensions	1500 mm (L) x 650 mm (W) x 1650 mm (H) and 2000mm (L) x 900 mm (W) x 1800 mm (H) for Bigger Version