

## Glass Bottle Beer Filling Machine BGCFS-series



This series machine adopts the current international double vacuum zed and high-pressure bubble injection technology to minimize oxygen containing in beer to improve greatly the beer taste. Accurate pressure control and automatic bottle detection function make sure the good quality. This equipment adopts the advanced German technology combining with the characteristics of beer production in domestic market which makes the machine with reliable working performance to complete the function of rinsing, filling, capping and disinfecting to realize the beer sterile filling environment. And the production can be adjusted from 2000b/h to 20000b/h.

| Model                           | BGCFS18-18-6                            | BGCFS 24-24-8                           | BGCFS 32-32-8                           |
|---------------------------------|-----------------------------------------|-----------------------------------------|-----------------------------------------|
| Production Capacity (500ml) b/h | 1000-2000BPH                            | 2000-3000BPH                            | 4000-5000BPH                            |
| Glass Bottle Diameter (mm)      | Ø50- Ø 90                               | Ø50- Ø 90                               | Ø50- Ø 90                               |
| Glass Bottle Height (mm)        | 150-320                                 | 150-320                                 | 150-320                                 |
| Rinsing Pressure (Mpa)          | 0.25-0.3                                | 0.25-0.3                                | 0.25-0.3                                |
| Filling Style                   | Isobar<br>Filling (double<br>vacuumize) | Isobar<br>Filling (double<br>vacuumize) | Isobar<br>Filling (double<br>vacuumize) |
| Suitable Cap                    | Crown Cover                             | Crown Cover                             | Crown Cover                             |
| Main Power (kw)                 | 4.9                                     | 4.5                                     | 5.5                                     |
| Total Weight(kg)                | 4500                                    | 6500                                    | 10000                                   |
| Dimension (mm)                  | 2520*2020*2700                          | 3000*2200*2800                          | 4160*2860*H2900                         |
| L*W*H                           |                                         |                                         |                                         |

| Model                           | BGCFS 40-40-10                    | BGCFS50-50-12                     |
|---------------------------------|-----------------------------------|-----------------------------------|
| Production Capacity (500ml) b/h | 5000-6000BPH                      | 6000-7000BPH                      |
| Glass Bottle Diameter (mm)      | Ø50- Ø 90                         | Ø50- Ø 90                         |
| Glass Bottle Height (mm)        | 150-320                           | 150-320                           |
| Rinsing Pressure (Mpa)          | 0.25-0.3                          | 0.25-0.3                          |
| Filling Style                   | Isobar Filling (double vacuumize) | Isobar Filling (double vacuumize) |
| Suitable Cap                    | Crown Cover                       | Crown Cover                       |
| Main Power (kw)                 | 8.5                               | 10                                |
| Total Weight(kg)                | 12000                             | 15000                             |
| Dimension (mm)                  | 4550*3250*H2900                   | 5620*3570*H2900                   |
| L*W*H                           |                                   |                                   |