

SED-TB Automatic Labeling Machine



It is widely used to produce the carbonated bottle, mineral water, pesticide bottle oil bottle cosmetics, wide-mouth bottle and hot fill bottle etc.

Beverage bottle, cosmetic bottle, medicine bottle, jar etc.

Lorem Ipsum is simply dummy text of the printing and typesetting industry. Lorem Ipsum has been the industry's standard dummy text ever since the 1500s, when an unknown printer took a galley of type and scrambled it to make a type specimen book.

Advantages of Labeling Machine

1. Special for multi-specifications product plane labeling (above). Labeling for paper or similar products
2. Equipped with bottle-dividing mechanism or paging machine to make objects enter labeling area equidistantly
3. The front segment splitting and closing mechanism can be added, and it can also be connected with the upper production line.
4. Sponge wheel automatic rolling label, make labeling more firm.
5. The main motor can be stepper motor or Panasonic servo motor, respectively. (According to customer needs).

Product Parameters

Voltage:	AC220v 50/60Hz
Power:	0.5KW/h
Labeling speed:	0-180 boxes/min (depending on label length)
Labeling accuracy:	+0.5mm
Printer speed:	0-250 times per minute (synchronized with labeling)
Applicable container range:	length 25-150 width 10-120 height 0-150
Applicable Label Range:	25-150 Length, 20-90 Height
Maximum label supply:	380 mm diameter paper roll inside 76mm
Transparency:	52% label spacing: 3-4 mm (+0.2 mm)
Tear Resistance:	Machine Direction: 25g/Zhang Lateral: 31g/Zhang
Transparency:	52% label spacing: 3-4 mm (+0.2 mm)