KDS-800 Strip Packaging Machine



The KDS-800 is a high speed strip packing Machine and has been designed to pack capsules, Tablets or similar products. The basic simplicity operation offer wide range product and high quality strip sealing.

Applicable industry: Pharmacy, Biotechnology, Health Supplements, Nutritional Supplements, natural food…etc.

Features:

- Compact size with all function and fast production.
- Used two roller sealing make around the pockets form a hermetic seal thus offering maximum shelf life to the product contained within strip pocket.
- Higher level Aluminum laminate material , more thick double side aluminum film sealing technology successfully isolate oxygen and humidity.
- It is very easy to exchange all the size change parts. It takes less than 30 minutes to finish.
- Main frame is covered with stainless steel. Easy clean.
- Apply to cGPM & PIC/S GMP standard.
- Automatic feeding, Sealing, Perforation ,Slitting and Cutting are done simultaneously. Therefore, its efficiency is high, meaning production cost is decreased due to reduction of labor cost.
- Compact and constructed simply, the machine can be maintained easily, operates with low noise.
- When packing operation is completed, the product shall be absolutely sealed and beautifully looked at. This certainly improve the quality of the product.

- User friendly design operators are getting operation on hand easily.
- With precise PID temperature control system successfully control roller in required working temperature.
- Adjustable cutting selection set up row cutting line (1~99).
- Unique slitting and cutting device make a beautiful appearance on strip cutting edge.
- Hot Stamping Device help stamp batch no. or expiry date. (Option)
- Perforation Device (Horizontal) tear strip easily. (Option)
- Miss Feed reject system, make sure products are feed into strip pocket other wise will reject automatically. (Option)

Technical data:

Capacity	**Max. 70,000 pcs/hr (Φ5 m/m TABLET)**
Pack Material	**ALUMINUM, COATED PAPER, COMPOUND FOIL, CELLOPHANE**
Line	**1~10**
Power Consumption	**2.5KW**
AIR Consumption	**6 kgf/ cm² , 200 ℓ/min**
Power Supply	**AC220V 50/60 Hz 1phase**
Machine Size (LxWxH)	**90 x 140 x 225 (cm)**
Packing size (LxWxH)	**110 x 160 x 175 (cm)**
Gross Weight	**600 kg**
Net Weight	**700 kg**