



## ➔ Wet Glue Labelling Machines

### ▣ LABELWET-150 - Wet Glue Labelling Machines - Automatic Wet Glue Labelling Machine



**Layout**



**E-Catalog**



**Video**

Fully Automatic, High Speed Labelling Machine Model LABELWET-150 in completely STAINLESS STEEL FINISH to meet current market requirement. LABELWET-150 is made for Labelling on many kind of round Vials, Bottles and other cylindrical products used by Pharmaceutical, Beverage, Food, Cosmetics, Ayurvedic, Breweries, Distilleries and other industries

LABELWET-150 is Economical, efficient, reliable and Low Cost Automatic Labelling Machine specially to suit the requirement of Pharmaceutical Industries having multiple products and sizes change over.

The machine also has Completely Stainless Steel Finish, No Bottle No Label system and No Label No Gluing system. Machine available with Optional Online Coding System, Pulse Counter, Safety Guard and Inkjet Coding System. The LABELWET-150 Model comes with simple user friendly operation and settings for Vials or Bottles with suitability to most of requirement in Pharmaceutical and allied industries to match individual requirement of customer with their specification and speed.



## BUILT-IN UNIQUE FEATURES :

- No Label - No Gluing System eliminating wastage of Glue
- No Product - No Label System eliminating wastage of Labels
- Synchronized speed of Label application with Gluing, Printing and Vial Feeding
- Fully Gear Drive System - No Chain Drive
- Easy Change over system with Low Cost Change Parts
- Suitable for Partial, Full Wrap Around and Overlap Labelling
- Fully Stainless Steel finish Machine
- Built in Turn Table at Infeed Side

## OPTIONAL FEATURES :

- Digital Counter
- Safety Guard
- A. C. Variable Frequency Drive System
- Online Contact Coding or Inkjet Coding System
- Tower Light showing the machine status / operation
- Special Sensing system for checking missing label on product suitable for Labels with UV Ink or UV Coating
- Low Vacuum - Machine Stop System

## TECHNICAL SPECIFICATIONS :

Label Height :	16 mm to 70 mm Standard*
Label Length :	45 mm to 120 mm Standard*
Vial Diameter :	15 mm to 85 mm*
Glue :	Cold Dextrine Base Glue or other glue which does not create any fibres or threading during rotation, water soluble glue is required
Electrical :	415 VAC 3 Phase or 220 VAC 1 Phase Power Supply through A.C. Variable Frequency Drive System(50/60 Hz)
Power :	2 H.P. With One Vacuum Pump
Speed :	Up to 150 Labels per minute depending on Product and Label Size
Conveyor height :	830-875 mm*
Overall dimension :	3050 mm(L) X 1200 mm(W) X 1100 mm (H)
Machine Direction of Movement :	Left to Right from operator side

\* Specification can be changed as per customers requirements