

## ***Automatic L-bar Sealing & Shrink Packing Machine BS-400LB+BMD-450B***



### **Application:**

Pharmaceutical, food, stationery, cosmetic, electronic products, toys, etc.

### **Technique parameter:**

Technical Data: BS-400LB+BMD-450B

- 1) Sealing type: L-sealing
- 2) Power supply: 380V/50-60Hz/3phase
- 3) Packing capacity: 15 - 35 packs/min
- 4) L-bar sealing size: 570x480 mm
- 5) Sealing height: 150 mm
- 6) Product size: width + height < 400mm, length + height < 480mm
- 7) Film type: center-folded polyolefin (POF) film
- 8) Max film size: 530mm (width) x 280mm(outer diameter)
- 9) Oven size: 1200(L) x 450(W) x 220(H) mm
- 10) Shrink tunnel conveyor speed: variable, max. 40 m/min
- 11) Shrink tunnel conveyor: rotating silicon coated rods
- 12) Power consumption: max. 8.5 kW
- 13) Working height: 780-850 mm
- 14) Air pressure: 0.5MPa (5 bar)
- 15) Sealing knife: Teflon coated alloyed knife with permanently heated bar
- 16) Main control components: Siemens PLC and touch screen, Omron temperature controller, relay and sensor
- 17) Machine main material: stainless steel
- 18) Machine dimension: 1600 x 770 x 1450mm 1600 x 600 x 1260mm
- 19) Machine weight: 450kgs

Layout:

